

THERMOPILE

Thermopile Sensor

OTP-628D2

Revision Date: 2018/09/20 (Rev.08)



The OTP-628D2 is a thermopile sensor in classic TO-46 housing. The sensor is composed of 116 elements of thermocouple in series on a floating micro-membrane having an active area of diameter 545 μm . The thermopile sensor provides nearly Johnson-noise-limited performance, which can be calculated by its ohmic series resistance. A thermistor with a lead connected to ground is also provided inside the TO package for ambient temperature reference.

- TO-46 metal housing
- Thermistor temperature reference included
- Low temperature coefficient of sensitivity
- Ideally suited for ear thermometers, miniature pyrometer.

Parameter	Typ	Unit	Conditions
Sensitivity	46	V/W	500K, 5-14 μm
TC of sensitivity	0.22 \pm 0.05	%/K	25°C
Thermopile Voltage	2.6 \pm 0.8	mV	Tb:50°C, Ta:25°C 5-14 μm
Active area in diameter	0.545	mm	
Resistance of thermopile	115 \pm 35	K Ω	25°C
TC of resistance	0.11 \pm 0.05	%/K	25°C
Time constant	20	ms	
Noise voltage	43	nV/Hz $^{1/2}$	r.m.s 300K
NEP	0.95	nW/Hz $^{1/2}$	500K, 5-14 μm
Normalized detectivity (D*)	0.9 \times 10 8	cm * Hz $^{1/2}$ /W	500K, 5-14 μm
Thermistor resistance	100 \pm 5%	K Ω	25°C
β value	3964 \pm 0.5%	K	25°C/100°C
Field of view	90	°	@50% target signal
Cut on wavelength	5.0 \pm 0.3	μm	@25°C, 50% transmittance

